SI Physics - Full Discipline Demo

Torque and Equilibrium - Digital

Final Report - Answer Guide


InstitutionScience Interactive UniversitySessionSI Physics - Full Discipline DemoCourseSI Physics - Full Discipline Demo

Instructor Sales SI Demo

Test Your Knowledge




Match each term to the best description.



Correct answers:

- 1 Static equilibrium 2 Torque 3 Center of mass 4 Radial distance
- 5 Line of action 6 Pivot point

Identify each statement as true or false.



Correct answers:

1 The rotational velocity must be zero during static equilibrium.

Torque is a vector quantity.

2

A force applied parallel to the moment arm produces the largest possible torque.

Torque is positive when it induces rotation in the clockwise direction.

Exploration

A force applied at a $90\ensuremath{^\circ}$ angle to the moment arm produces the largest possible torque.

O True			•
False			



Torque can be fou	nd using the equation	
$\bigcirc \ \ \tau = rF_{\perp}$		
$\bigcirc \ \ \tau = r_\bot F$		
$\circ \ au = rF\sin(heta)$		
All of the above		~
The is the avenue weighted according	erage position of all parts of the object on the object of the object of the mass.	or system
center of gravity	,	
center of mass		✓
pivot point		
None of the above	ve	
The moment of inc	ertia depends on how the of an obje	ect is distributed.
gravity		
inertia		
o mass		~
 All of the above 		
is the rotatio	onal equivalent of force and causes rotati	ional motion.
Center of mass		
Moment of inerti	ia	
O Torque		~
All of the above		

s	tatic equilibr	ium occurs	when the _	is zero.				
	o net force							
	o net torque							
	velocity							
	All of the ab	oove					~	
Exercis	e 1							
at the bea	wo objects w m center of r our answer.				-			-
done by unadial distribution objects are the bricks changed lof the unathe pivot	masses can be stillizing the too ance r can be see on different recorded in Expectages the range of the course the management of the course the management as the management of the course of the co	rque equation adjusted subsides of the Data Table 7 adial distance changed by the control of the	on $\tau = r \times F$. Tuch that the tender private point, remained concerning the point of the private of the privat	Though the grorques have this ensures on the stant at 20 led. The system of sed with the sed wit	avitational for equal magni equilibrium is kg, but the to em could still the bricks. T	orces are tudes. As s reached orque due be balan he bricks	different suming t d. The ma e to the b ced as th moved c	, the he iss of ricks he mass loser to
Describe h	now torque a	nd equilibr	ium determi	ne the mass	of an unkn	own obje	ect.	
Equilibrium requires that the torque due to all forces acting on a balance add up to zero. Therefore, the torque due to the weight of a single object resting on the balance can be determined if the torques due to any other objects acting on the balance are known. Once the torque due to the weight of the unknown object is determined, the mass can be found using the definition of torque $\tau = r \times F$, and the definition of weight $F = w = mg$ and solving for the mass.								
Data Table 1: Determining the Mass of a Mystery Object (SAMPLE ANSWER BELOW)								
Mystery object	Object distance (m)	Brick mass (kg)	Brick distance (m)	Brick torque (Nm)	Object mass (kg)	F _{object} (N)	F _{bricks}	F _{pivot} point (N)



Α	1.00	20	1.00	-196.20	20	-196.20	-196.20	392.40
В	1.00	20	0.25	-49.05	5	-196.20	-49.05	245.25
С	1.00	20	0.75	-147.15	15	-196.20	-147.15	343.35
D	1.00	20	0.50	-98.10	10	-196.20	-98.10	294.30

Competency Review

Center of mass Moment of inertia Torque All of the above The spans the distance from the to the location of the applied force. moment arm; pivot point moment of inertia; center of mass torque; center of mass None of the above A net force of zero is the only requirement for static equilibrium. True False Torque can be calculated if the and angular acceleration are known. mass moment arm	ne to the location of the applied rement for static equilibrium.	distance.	aiai
The spans the distance from the to the location of the applied force. moment arm; pivot point moment of inertia; center of mass torque; center of mass None of the above A net force of zero is the only requirement for static equilibrium. True False Torque can be calculated if the and angular acceleration are known. mass	ne to the location of the applied rement for static equilibrium.	Center of mass	
The spans the distance from the to the location of the applied force. moment arm; pivot point	ne to the location of the applied rement for static equilibrium.	 Moment of inertia 	
The spans the distance from the to the location of the applied force. moment arm; pivot point	rement for static equilibrium.	Torque	~
force. moment arm; pivot point	rement for static equilibrium.	 All of the above 	
 moment of inertia; center of mass torque; center of mass None of the above A net force of zero is the only requirement for static equilibrium. True False Torque can be calculated if the and angular acceleration are known. mass 	rement for static equilibrium. ✓		
 torque; center of mass None of the above A net force of zero is the only requirement for static equilibrium. True False Torque can be calculated if the and angular acceleration are known. mass 	· ·	moment arm; pivot point	~
 None of the above A net force of zero is the only requirement for static equilibrium. □ True □ False ✓ Torque can be calculated if the and angular acceleration are known. □ mass 	· ·	moment of inertia; center of mass	
A net force of zero is the only requirement for static equilibrium. True False Torque can be calculated if the and angular acceleration are known. mass	· ·	torque; center of mass	
 True False ✓ Torque can be calculated if the and angular acceleration are known. mass 	· ·	None of the above	
Torque can be calculated if the and angular acceleration are known. mass		A net force of zero is the only requirement for static equilibrium.	
Torque can be calculated if the and angular acceleration are known.		True	
mass	and angular acceleration are known. ✓	False	✓
mass	and angular acceleration are known.	•	
	✓	Torque can be calculated if the and angular acceleration are known.	
o moment arm	✓	mass	
I .	✓	o moment arm	
moment of inertia		moment of inertia	~
None of the above		 None of the above 	



motion.	
O True	
○ False	✓
A door is pushed with a force of 5 N at a distance of 30 cm from the hing. The torque is	je.
○ 6 N/m	
○ 150 N m	
○ 1.50 N m	✓
None of the above	
A 40 cm ruler with non-uniform mass is hung from its center of mass, at cm. A force is applied at the 40 cm mark of the ruler. The length of the moment arm is	21
O 40	
O 19	✓
© 21	
None of the above	
A 30 cm ruler is found to have a center of mass of 15.6 cm. The percent error of the center of mass is, if the ruler is assumed to have uniformass.	rm
0.48%	
○ 0.52%	
O 4%	✓
None of the above	

Torque is the rotational equivalent of force and causes translational




A seesaw sits in static equilibrium. A child with a mass of 30 kg sits 1 m away from a pivot point. Another child sits 0.75 m away from the pivot point on the opposite side. The second child's mass is ____ kg.

203040None of the above

Extension Questions

In cycling, the torque generated about the crank axis is determined by the magnitude of the force from a foot pushing the pedal as well as the angle between the crank arm and the force vector. The diagram shows the 17.5 cm crank pedal at two positions: 90 degrees and 135 degrees. What is the torque at each of the points if the foot applies a force of 800 N? Which position creates the larger torque? Note: Use the angle between the force application and crank arm in your calculations.



(SAMPLE ANSWER BELOW)

At 90 degrees, the torque is: tau=r*F*SIN(90)=0.175*800*1=140 N*m. At 135 degrees, the torque is: tau=r*F*SIN(135-90)=0.175*800*SIN(45)=99 N*m. Thus, the 90 degree position yields the greater torque. Note: The angle for the second calculation is 135-45 degrees due the geometry of the system. You must use the angle between the applied force and the crank. SIN(135) would give the component of the force parallel to the crank arm.